

T1000

T1000 Specifications

TOPBAND 拓邦



- Capacity: 1002Wh
- Rated Power: 1200W
- Surge Power: 2400W

- Switchable AC Input Power (300W for longer cycle life, 900W for fast charging)
- One-Button Off
- Eco Mode (AC shuts down automatically when idle)
- LED Light (with SOS mode, 3W)
- 1 extra battery (1kWh x 1) via cable connection
- EPS Mode (30ms)
- APP Port (app control available)
- LiFePO4 32700 Battery, 1500 cycle life and safer

Input/Output Ports

| | |
|---------------------------------|-----------------------------|
| AC Output Port (4 ports) | 1200W Max |
| USB-C (2 ports) | 5V/9V/12V/15V/20v, SA, 100W |
| USB-A QC (2 ports) | 5V/9V/12V, 1.5A, 18W |
| USB-A (2 ports) | 5V, 2.4A, 12W |
| Cigarette Lighter (2 ports) | 13.6V, 10A |
| DC 5521 Port (2 ports) | 13.6V, 3A |
| Wireless Charging Pad (2 ports) | 15W |
| AC Input Port (2 ports) | 900W/300W |
| Solar Input Port (2 ports) | 600W Max |

T1000 Specifications

TOPBAND 拓邦



- Capacity: 1002Wh
- Rated Power: 1200W
- Surge Power: 2400W

T2000

T2000 Specifications

TOPBAND 拓邦



- Capacity: 2016Wh
- Rated Power: 2000W
- Surge Power: 4000W

- AC Quick Charge (2 hours to 100%)
- Ventilation Structure on the Bottom
- One-Button Off
- Eco Mode (AC shuts down automatically when idle)
- LED Light (with SOS mode, 3W)
- 2 extra batteries (2kWh x 2) via cable connection
- EPS Mode (30ms)
- APP Port (app control available)
- LiFePO4 32700 Battery, Longer cycle life and safer

Input/Output Ports

| | |
|-----------------------------|---|
| AC Output Port (6 ports) | 2000W Max (6 ports for USA & Japan, 4 ports for Europe) |
| USB-C (6 ports) (2 ports) | 5V/9V/12V/15V/20v, SA, 100W |
| USB-A QC (2 ports) | 5V/9V/12V, 1.5A, 18W |
| USB-A (2 ports) | 5V, 2.4A, 12W |
| Cigarette Lighter (1 ports) | 13.6V, 10A |
| RV Port (1 ports) | 13.6V, 40A |
| DC 5521 Port (2 ports) | 13.6V, 3A |
| AC Input Port | 2 Hours to 100% |
| Solar Input Port | 10-25V |